
# Product Inquiry Hotline (510) 226-1800





ARISTA has developed a broad range of products for the pharmaceutical and biotech manufacturing process. No matter batch manufacturing process or continuous manufacturing process, such as API synthesis, crystallization, blending, granulation, tablet press and coating, you will find ARISTA has all computing platforms for either manufacturing process automation or KPI visualization in every process in the cleanroom.



## WHO WE ARE

ARISTA Corporation was founded in 1994 and has been providing computing platforms to various industries, like Pharmaceutical and biotech, Oil and Gas, Food and Beverage, Automotive, Logistic, FMCG, etc. ARISTA is committed to providing the most reliable computing platforms to optimize our customers' manufacturing automation systems. "Talk to us. We listen." makes ARISTA a dependable and accountable partner to all our customers.

## WHY CHOOSE US

Longevity

Flexible Customization

Revision Control





sales@goarista.com www.aristaipc.com



### **Pharmaceutical and Biotech Solutions**

Feature Products

### **Operator Workstations**

### **Mobile Operator Workstation and Computer Cart**



### **AMW-1121AX**

Industrial Stainless Steel NEMA 4X / IP66 Wi-Fi Mobile Operator Terminal Stations



- 21.5" Active Matrix TFT LCD Display
- Native Resolution at 1920 x 1080
- 2.6/3.4 i7-6600U Intel E3845 1.91GHz ATOM CPU
- Up to 16GB DDR4 DIMM SO-DIMM Memory Wi-Fi Module Included
- Battery Option
- Projected Capacitive Touchscreen
- NEMA 4X / IP66 Stainless Steel Fully Closed Enclosure
- Waterproof Keyboard and Pointing Device
- ThinManager Ready Version Available
- Three Keyboard Option



### **AMW-1321AX**

by Computer Cart style Industrial Stainless Steel NEMA 4X / IP66 Wi-Fi Mobile Operator Terminal Stations

- 21.5" Active Matrix TFT LCD Display
- Native Resolution at 1920 x 1080
- Intel ATOM CPU/ Intel 6th Gen Core-I CPU
- Up to 8GB DDR3 / Up to 16GB DDR4 SO-DIMM
- · Wi-Fi Module Included
- Battery Option
- Projected Capacitive Touchscreen
- NEMA 4X / IP66 Stainless Steel Fully Closed Enclosure
- · Waterproof Keyboard and Pointing Device
- ThinManager Ready Version Available
- Three Keyboard Options

### **AMW-2219AX**

Industrial Stainless Steel NEMA 4X / IP66 Wi-Fi Mobile Operator Terminal Stations

### • 2 x 19" Active Matrix TFT LCD Display

- Native Resolution at 1280 x 1024
- Intel ATOM CPU/ Intel 6th Gen Core-I CPU
- Up to 8GB DDR3/ Up to 16GB DDR4 DIMM
- Wi-Fi Module Included
- Battery Option
- Projected Capacitive Touchscreen
- NEMA 4X / IP66 Stainless Steel Fully Closed Enclosure · Waterproof Keyboard and Pointing Device

Phone: (510) 226-1800

Fax: (510) 405-8437

- ThinManager Ready Version Available
- Three Keyboard Options

### **AMW-2224AX**

Industrial Stainless Steel NEMA 4X / IP66 Wi-Fi Mobile Operator Terminal Stations

- 2 x 24" Active Matrix TFT LCD Display
- Native Resolution at 1280 x 1024
- Intel ATOM CPU/ Intel 6th Gen Core-I CPU
- · Up to 8GB DDR3/ 16GB DDR4 SO-DIMM
- Wi-Fi Module Included
- Battery Option
- Projected Capacitive Touchscreen
- NEMA 4X / IP66 Stainless Steel Fully Closed Enclosure Waterproof Keyboard and Pointing Device
- ThinManager Ready Version Available
- Three Keyboard Options



### **AMW-2318AX**

Industrial Stainless Steel NEMA 4X / IP66 Wi-Fi Mobile Operator Terminal Stations


- 3 x 18.5-inch Displays
- Native Resolution at 1920 x 1080 · 2.6/3.4 GHz i7-6600U2.4/3.0 GHz i5-6300U.
- 1.6 GHz Celeron-3855U
- Up to 32GB DDR4 Memory
- Wi-Fi Module Included
- Battery Option
- Projected Capacitive Touchscreen
- NEMA 4X / IP66 Stainless Steel Fully Closed Enclosure
- Waterproof Keyboard and Pointing Device
- ThinManager Ready Version Available
- Three Keyboard Option

### **Operator Workstations**

### **Operator Terminal Workstation**

### Wall Mount 1

ARP-3821AX-AMA Wall Mount 21.5-inch Capacitive Touch Screen Operator Workstation (Wall Mount 1)



- · Intel ATOM CPU/ Intel 6th Gen Core-I CPU
- · Up to 8GB DDR3 / Up to 16GB DDR4 SO-DIMM
- Stainless Steel Fully Closed Enclosure
- Meets NEMA 4X / IP66 Protection Requirements Stainless Steel Wall Mount Mounting Brackets Included
- Waterproof Keyboard and Pointing Device
- Three Keyboard Options
- ThinManager Ready Version Available
- Cables for 24V DC Input and Gigabit Ethernet (RJ45)

48460 Lakeview Blvd,

Fremont, CA 94538







### ARP-3821AX-AMA

Adjustable Height Wall Mount 21.5-inch Capacitive Touch Screen Operator Workstation (Wall Mount 2)

- 21.5" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch Screen
- · Intel ATOM CPU/ Intel 6th Gen Core-I CPU
- Up to 8GB DDR3 / Up to 16GB DDR4 SO-DIMM Stainless Steel Fully Closed Enclosure
- Meets NEMA 4X / IP66 Protection Requirements
- Adjustable Height Wall Mount Mounting Brackets Included
- Waterproof Keyboard and Pointing Device

Cables for 24V DC Input and Gigabit Ethernet (RJ45)

Three Keyboard Options

sales@goarista.com

www.aristaipc.com

ThinManager Ready Version Available

Feature Products

**Operator Workstations** 

### **Operator Terminal Workstation**



### **ARP-5500AX-AMA Series** (ARP-5515AX-AMA / ARP-5517AX-AMA / ARP-5519AX-AMA)

Wall Mount 15/17/19-inch Resistive Touch Screen Operator Workstation (Ceiling Mount)

ARP-5515AX-AMA	ARP-5517AX-AMA	ARP-5519AX-AMA	
15" LCD, 1024 x 768 Resolution	17" LCD, 1280 x 1024 Resolution	19" LCD, 1280 x 1024 Resolution	
S-Wire Resistive Touch Screen     Intel ATOM CPU/ Intel 6th Gen Core-I CPU     Up to 8GB DDR3 / Up to 16GB DDR4 SO-DIMM			

- Stainless Steel Fully Closed Enclosure
- Meets NEMA 4X / IP66 Protection Requirements Stainless Steel Wall Mount Mounting Brackets Included
- Waterproof Keyboard and Pointing Device
- Three Keyboard Options
- ThinManager Ready Version Available
- Cables for 24V DC Input and Gigabit Ethernet (RJ45)



### AMA-7000AX Series (AMA-7015AX / AMA-7019AX / AMA-7021AX) Recessed Wall / Wall Mount 15/19/21.5-inch Resistive Touch Screen Operator Workstation

AMA-7015AX	AMA-7019AX	AMA-7021AX
15" LCD, 1024 x 768	19" LCD, 1280 x 1024	21.5" LCD, 1920 x 1080
Resolution     Projected Canacity	Resolution	Resolution

### • 5-Wire Resistive Touch Screen

- Intel ATOM CPU/ Intel 6th Gen Core-I CPU
- · Up to 8GB DDR3 / Up to 16GB DDR4 SO-DIMM
- Stainless Steel Fully Closed Enclosure
- Meets NEMA 4X / IP66 Protection Requirements
- · Recessed Wall / Wall Mount
- Waterproof Keyboard and Pointing Device
- Three Keyboard Options
- ThinManager Ready Version Available

### ΔΜΔ-7421ΔΧ Pedestal Mount 21.5 inch Resistive Touch Screen Operator Workstation (1)(1)(1) • 21.5" LCD, 1920 x 1080 Resolution Projected Capacitive Touch Screen Intel ATOM CPU/ Intel 6th Gen Core-I CPU Up to 8GB DDR3 / Up to 16GB DDR4 SO-DIMM Stainless Steel Fully Closed Enclosure Meets NEMA 4X / IP66 Protection Requirements Stainless Steel Pedestal Included Waterproof Keyboard and Pointing Device Three Keyboard Options ThinManager Ready Version Available Cables for 24V DC Input and Gigabit Ethernet (RJ45)

**Operator Workstations Operator Terminal Workstation Powered By PoE** 

### Wall Mount 1 Field Replaceable (Display / Keyboard)

### ARP-3821AX-AMA-E01

Wall Mount 21.5-inch Capacitive Touch Screen Operator Workstation Powered by 802.3bt Type 3/4 PoE (Wall Mount 1)



- Projected Capacitive Touch Screen
- Intel E3845 ATOM CPU
- Up to 8GB DDR3
- Stainless Steel Fully Closed Enclosure
- Meets NEMA 4X / IP66 Protection Requirements
- Stainless Steel Wall Mount Mounting Brackets Included
- · Waterproof Keyboard and Pointing Device
- Three Keyboard Options
- ThinManager Ready Version Available • Powered By 802.3bt Type 3/4 PoE

### Meets NEMA 4X / IP66 Protection Requirements · Adjustable Height Wall Mount Mounting Brackets Included Waterproof Keyboard and Pointing Device Three Keyboard Options

 ThinManager Ready Version Available Powered By 802.3bt Type 3/4 PoE

ARP-3821AX-AMA-E01

• 21.5" LCD, 1920 x 1080 Resolution

Projected Capacitive Touch Screen

Stainless Steel Fully Closed Enclosure

Intel E3845 ATOM CPU

Up to 8GB DDR3

(Wall Mount 2)

Adjustable Height Wall Mount 21.5-inch Capacitive Touch

### Ceiling Mount Field Replaceable (Display / Keyboard)

### ARP-5500AX-AMA-E01 Series

(ARP-5515AX-AMA-E01 / ARP-5517AX-AMA-E01 / ARP-5519AX-AMA-E01) Wall Mount 15/17/19-inch Resistive Touch Screen Operator Workstation Powered by 802.3bt Type 3/4 PoE (Ceiling Mount)

ARP-5515AX- AMA-E01	ARP-5517AX- AMA-E01	ARP-5519AX-AMA-E01
15" LCD, 1024 x 768 Resolution	17" LCD, 1280 x 1024 Resolution	19" LCD, 1280 x 1024 Resolution
Up to 8GB DDR3		Up to 8GB DDR3 / Up to 16GB DDR4 SO-DIMM
S-Wire Resistive To     Intel E3845 ATOM		

- Stainless Steel Fully Closed Enclosure
- Meets NEMA 4X / IP66 Protection Requirements
- Stainless Steel Wall Mount Mounting Brackets Included
- Waterproof Keyboard and Pointing Device
- Three Keyboard Options
- ThinManager Ready Version Available
- Powered By 802.3bt Type 3/4 PoE



### Pedestal Mount

### AMA-7421AX-E01

Pedestal Mount 21.5-inch Resistive Touch Screen Operator Workstation Powered by 802.3bt Type 3/4 PoE

- 21.5" LCD, 1920 x 1080 Resolution
- · Projected Capacitive Touch Screen
- Intel E3845 ATOM CPU
- Up to 8GB DDR3
- Stainless Steel Fully Closed Enclosure
- Meets NEMA 4X / IP66 Protection Requirements
- Stainless Steel Pedestal Included
- Waterproof Keyboard and Pointing Device
- Three Keyboard Options
- ThinManager Ready Version Available Powered By 802.3bt Type 3/4 PoE



1 1





sales@goarista.com www.aristaipc.com







## 

## Pharmaceutical and Biotech Solutions

Feature Products

**Operator Workstations** 

### **KVM Operator Workstation**

### AMA-2121AX-KVM

Wall Mount Waterproof KVM Extender Integrated 21.5-inch LCD Remote KVM Workstation up to a 330 feet single CAT6 cable connection to the computer

- 21.5-inch HFD LCD Display
- 1920 x 1080 Resolutions
- Projected Capacitive Touch Screen
   NEMA 4X / IP66 Waterproof Stainless-Steel Enclosure
- Single CAT6 cable connection to KVM Transmitter
- True one-cable solution up to 100 meters CAT6 cable
- · No Power Supply is required
- Accessible Waterproof USB Ports Available
- Built-in a 1-port 100BaseT Ethernet pass-through
- 3x Keyboard and Pointing Device options
  Left and Right Mouse Tray

- 21.5-inch HFD LCD Display
  1920 x 1080 Resolutions
  - Projected Capacitive Touch Screen

AMA-7421AX-KVM

- NEMA 4X / IP66 Waterproof Stainless-Steel Enclosure
- Single CAT6 cable connection to KVM Transmitter

21.5-inch Remote KVM Workstation up to a 330 feet single CAT6 cable connection to the computer

- True one-cable solution up to 100 meters CAT6 cable
- No Power Supply is required
- Accessible Waterproof USB Ports Available
- 3x Keyboard Options
- · HDMI & USB Extender is included
- 3 to 1 / 4 to 1 KVM Switch Extender Options




**Industrial Panel PCs** 

### Waterproof Panel PCs



### **ARP-3821AX**

NEMA 4X Waterproof Panel PC with 21.5-inch Projected Capacitive Touch



- Projected Capacitive Touch
- Stainless Steel Enclosure
- Intel E3845 ATOM CPU/ Intel i7-6600U CPU
- Up to 8GB DDR3/ Up to 16GB DDR4 SO-DIMM
- 1x Gigabit Ethernet
- 2x USB 2.0 ports
- Optional 2.5" SSD
- Wi-Fi Connectivity (Optional)
- 24VDC Operating Voltage



### ARP-5500AX Series (ARP-5515AX / ARP-5517AX / ARP-5519AX)

NEMA 4X Waterproof Panel PC with 15/17/19-inch Resistive Touch Screen

ARP-5515AX	ARP-5517AX	ARP-5519AX	
15" LCD,         17" LCD,         19" LCD,           1024 x 768         1280 x 1024         1280 x 1024           Resolution         Resolution         Resolution			
Resolution     Resolution     Resolution       • 5-Wire Resistive Touch       • Stainless Steel Enclosure       • Intel E3845 ATOM CPU/ Intel i7-6600U CPU       • Up to 8GB DDR3/ Up to 16GB DDR4 SO-DIMM       • 1x Gigabit Ethernet       • 2x USB 2.0 ports       • Optional 2.5" SSD			

### 24VDC Operating Voltage



### ARP-5542AX

NEMA 4X Waterproof Panel PC with 42-inch IR Touch Screen

• 42" LCD, 1920 x 1080 Resolution

- 5-Wire Resistive Touch
- Stainless Steel Enclosure
- Intel E3845 ATOM CPU
- Up to 8GB DDR3
- 1x Gigabit Ethernet
- 2x USB 2.0 ports
- Optional 2.5" SSD
- · Wi-Fi Connectivity (Optional)
- 24VDC Operating Voltage

### **Industrial Panel PCs**

### Waterproof Panel PCs Powered By PoE

### ARP-3821AX-E01

NEMA 4X Waterproof Panel PC with 21.5" PCAP Touch Screen Powered By 802.3bt Type 3/4 PoE

- 21.5" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch Screen
   Stainless Steel Enclosure
- Intel E3845 ATOM CPU
- 8GB DDR3 SO-DIMM
- 1x Gigabit Ethernet
- 2x USB 2.0 ports
- Powered By 802.3bt Type 3/4 PoE



### ARP-5500AX-E01 Series

NEMA 4X Waterproof Panel PC with 15/17/19" Resistive Touch Screen Powered by 802.3bt Type 3/4 PoE

ARP-5515AX-E01	ARP-5517AX-E01	ARP-5519AX-E01	
15" LCD, 1024 x 768 Resolution	17" LCD, 1280 x 1024 Resolution	19" LCD, 1280 x 1024 Resolution	
Up to 8GB DD	8GB DDR3 SO-DIMM		
S-Wire Resistive Touch     Stainless Steel Enclosure			

- Intel E3845 ATOM CPU
- 1x Gigabit Ethernet
- 2x USB 2.0 ports
- Powered By 802.3bt Type 3/4 PoE





48460 Lakeview Blvd, Fremont, CA 94538



sales@goarista.com www.aristaipc.com



**Industrial Panel PCs** 

**Large Format Panel PCs** 

### **ARP-3855BP**

- VESA Mount Panel PC with 55-inch PCAP Touch Screen
- · 55" LCD, 1920 x 1080 Resolution
- Removable CPU Module Intel E3845 ATOM CPU
- Up to 8GB DDR3 Memory
- Optional 2.5" SSD
- Dual Gigabit Ethernet
- 1 x R232/422/485
- 1 x USB 3.0. 3 x USB 2.0 ports
- Auxiliary VGA, HDMI Inputs
- IR Remote Control
- Optional Wall Mount Bracket



### ARP-5542AX

- NEMA 4X Waterproof Panel PC with 42-inch IR Touch Screen
- · 42" LCD, 1920 x 1080 Resolution
- 5-Wire Resistive Touch
- Stainless Steel Enclosure
- Intel E3845 ATOM CPU
- Up to 8GB DDR3
- 1x Gigabit Ethernet 2x USB 2.0 ports
- Optional 2.5" SSD
- Wi-Fi Connectivity (Optional)
- 24VDC Operating Voltage



### **Industrial Panel PCs**

### **Hazardous Locations Panel PCs**



### ARP-2200AP-G01 Series (ARP-2215AP-G01 / ARP-2217AP-G01 / ARP-2219AP-G01 / ARP-2221AP-G01)

Panel Mount Panel PC with 15/17/19/21.5-inch 5-Wire Resistive Touch for Use in Class I, **Division 2 Hazardous Locations** 

ARP-2215AP	ARP-2217AP	ARP-2219AP	ARP-2221AP
-G01	-G01	-G01	-G01
15" LCD,	17" LCD,	19" LCD,	21.5" LCD,
1024 x 768	1280 x 1024	1280 x 1024	1920 x 1080
Resolution	Resolution	Resolution	Resolution

- 5-Wire Resistive Touch
- Aluminum or Stainless-Steel Bezel
- Intel i7-3612QM CPU Up to 16GB DDR3 SO-DIMM
- Optional 2.5" SSD
- Dual Gigabit Ethernet
- 2 x RS-232/422/485 BIOS Selectable
- 2 x USB 3.0, 4 x USB 2.0 ports
- 24VDC Operating Voltage
- · UL Class 1 Division 2 explosion proof certification

**Industrial Displays** 

Wall Mount VESA Monitors

### **ADM-2155BP**

55-inch VESA Mount Projected Capacitive Touch Display

- 55" LCD, 1920 x 1080 Resolution
- Flush Bezel Design
- · Projected Capacitive Touch USB Touch Interface
- · VGA / DVI / HDMI Input
- Available HDMI 100 meters extender option
- Enclosure meets NEMA IP50 requirements
- VESA Mount, Optional Wall Mount Bracket
- · 110~220VAC Input







sales@goarista.com www.aristaipc.com



Phone: (510) 226-1800 Fax: (510) 405-8437

- 21.5" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch Stainless Steel Enclosure
- Intel E3845 ATOM CPU/ Intel i7-6600U CPU
- 1x Gigabit Ethernet
- 2x USB 2.0 ports

- UL Class 1 Division 2 explosion proof certification



### **ARP-5500AX Series**

(ARP-5515AX / ARP-5517AX / ARP-5519AX) NEMA 4X Waterproof Panel PC with 15/17/19-inch Resistive Touch Screen for Use in Class I, Division 2 Hazardous Locations

ARP-5515AX	ARP-5517AX	ARP-5519AX		
15" LCD,	17" LCD,	19" LCD,		
1024 x 768	1280 x 1024	1280 x 1024		
Resolution Resolution Resolution				
5-Wire Resistive Touch				

- Stainless Steel Enclosure
- Intel E3845 ATOM CPU/ Intel i7-6600U CPU • Up to 8GB DDR3/ Up to 16GB DDR4 SO-DIMM
- 1x Gigabit Ethernet
- 2x USB 2.0 ports
- Optional 2.5" SSD
- 24VDC Operating Voltage
- UL Class 1 Division 2 explosion proof certification
- · Up to 8GB DDR3/ Up to 16GB DDR4 SO-DIMM
- · Optional 2.5" SSD
- 24VDC Operating Voltage

NEMA 4X Waterproof Panel PC with 21.5-inch Projected Capacitive Touch for Use in Class I, Division 2

**ARP-3821AX** Hazardous Locations

### **Pharmaceutical and Biotech Solutions**

· 42-inch LCD Display, 1920 x 1080 resolutions

Enclosure meets NEMA 4X / IP65 requirements

Single CAT6 cable connection to KVM Transmitter

Built-in a 1-port 100BaseT Ethernet pass-through

Integrated VGA & RS-232 Extender Option:

· Adjustable equalization and gain control

· True one-cable solution up to 100 meters CAT6 cable

Built-in a 2-port USB 2.0 hub to support multiple USB devices.

• Video signal transmission length up to 1,000 ft (330m) over

· De-skew compensation available for RGB delay control

5-Wire Resistive Touch Screen

• 24VDC Input

CAT5e cable

· 24VDC Input

Waterproof Stainless-Steel Enclosure

Integrated HDMI & USB Extender Option

Feature Products

ADM-5842AX

Display Monitor

Waterproof 42-inch KVM

Extender Integrated LCD

### **Industrial Displays**

### Waterproof Touch Screen Monitors



### ADM-2121AX

Waterproof 21.5-inch KVM Extender Integrated LCD Display Monitor

- · 21.5-inch LCD Display, 1920 x 1080 resolutions
- · Project Capacitive Touch Screen supports multi-touch
- Waterproof Stainless-Steel Enclosure
- Enclosure meets NEMA 4X / IP65 requirements
- Single CAT6 cable connection to KVM Transmitter
- Powered by Transmitter
- · Built-in a 2-port USB 2.0 hub to support multiple USB devices. Built-in a 1-port 100BaseT Ethernet pass-through

### ADM-5500AX Series (ADM-5515AX / ADM-5517AX / ADM-5519AX)

Waterproof 15/17/19-inch KVM Extender Integrated LCD Display Monitor

ADM-5515AX	ADM-5517AX	ADM-5519AX	
15-inch	17-inch	19-inch	
LCD Display,	LCD Display,	LCD Display,	
1024 x 768	1280 x 1024	1280 x 1024	
resolutions	resolutions	resolutions	
- E Wire Desistive Touch Screen			

- istive Touch Screen 5-Wire Res
- Waterproof Stainless-Steel Enclosure · Enclosure meets NEMA 4X / IP65 requirements

### Integrated HDMI & USB Extender Opti

- Single CAT6 cable connection to KVM Transmitter
- True one-cable solution up to 100 meters CAT6 cable,
- no power supply is required
- Powered by Transmitter
- Built-in a 2-port USB 2.0 hub to support multiple USB devices.
- Built-in a 1-port 100BaseT Ethernet pass-through

### grated VGA & RS-232 Extender Optior

- Video signal transmission length up to 1,000 ft (330m) over CAT5e cable
- Adjustable equalization and gain control · De-skew compensation available for RGB delay control
- 24VDC Input

### **Industrial Extenders**

ARD-1007-A00-RX

external power supply

IR signals

4K HDMI, USB Decoder / Receiver

True one cable 330 feet extension solution

· Decodes HDMI, USB, 10/100 LAN, RS-232,

Powered by Transmitter, does not require

· Provides 12VDC/1A power source

### **KVM/KVM Switch Extenders**

ARD-1007 🚛

RISTA

### ARD-1007-A00-TX 4K HDMI. USB Encoder / Transmitter

- True one cable 330 feet extension solution · Encodes HDMI, USB, 10/100 LAN, RS-232, IR signals
- Power Source Equipment provides power to receiver



ARISTA ARD-0301-A00-TX 3x1HDMI + US8 KV

ARD-0301-A00-TX 3 to 1 KVM Switch Transmitter

- True one cable 330 feet extension solution
- Encodes 3 to 1 HDML USB signals
- · Power Source Equipment provides power to receiver

ARISTA ARD-0401-A00-TX Transmitter

ARD-0401-A00-TX 4 to 1 KVM Switch Transmitter

True one cable 330 feet extension solution

Encodes 4 to 1 HDMI. USB signals

· Power Source Equipment provides power to receiver



ARD-1007-A02-RX HDMI, USB KVM Switch Extension Receiver

True one cable 330 feet extension solution

 Decodes 3 to 1 / 4 TO 1 HDML USB KVM Switch Signals · Powered by Transmitter, does not require external power supply



48460 Lakeview Blvd, Fremont, CA 94538



sales@goarista.com www.aristaipc.com





**Industrial Extenders** 

KVM/KVM Switch Extenders

### AMA-2121AX-KVM

Wall Mount Waterproof KVM Extender Integrated 21.5-inch LCD Remote KVM Workstation up to a 330 feet single CAT6 cable connection to the computer

- 21.5-inch HFD LCD Display
- 1920 x 1080 Resolutions
- Projected Capacitive Touch Screen
- NEMA 4X / IP66 Waterproof Stainless-Steel Enclosure
- · Single CAT6 cable connection to KVM Transmitter True one-cable solution up to 100 meters CAT6 cable
- No Power Supply is required Accessible Waterproof USB Ports Available
- Built-in a 1-port 100BaseT Ethernet pass-through
- · 3x Keyboard and Pointing Device options
- · Left and Right Mouse Tray

### **Industrial Extenders**

**KVM Extender Integrated Displays** 

### ADM-1800AP-00A/00E Series

(ADM-1819AP-00A/00E / ADM-1821AP-00A/00E) Panel Mount KVM Extender Integrated 19/21.5-inch LCD Touch Display Monitor. True one-cable solution up to 100 meters CAT6 cable, no power supply is required

### ADM-1819AP-00A/00E ADM-1821AP-00A/00 19 inch LCD Display, 21.5 inch LCD Display, 1280 x 1024 resolutions 1920 x 1080 resolutions

5-Wire Resistive Touch Screen

- · Powder Coated Aluminum or Stainless-Steel Bezel
- Bezel meets NEMA 4X / IP66 requirements · Built-in a 2-port USB 2.0 hub to support multiple USB
- devices
- · Built-in a 2-port 100BaseT Ethernet pass-through hub Single CAT6 cable connection to KVM Transmitter No Power Supply is required

**Industrial Extenders** 

KVM Extender Integrated Displays

### AMA-7421AX-KVM

21.5-inch Remote KVM Workstation up to a 330 feet single CAT6 cable connection to the computer

- 21.5-inch HFD LCD Display
- 1920 x 1080 Resolutions
- Projected Capacitive Touch Screen NEMA 4X / IP66 Waterproof Stainless-Steel Enclosure
- Single CAT6 cable connection to KVM Transmitter
- · True one-cable solution up to 100 meters CAT6 cable
- No Power Supply is required
- Accessible Waterproof USB Ports Available
- 3x Keyboard Options
- HDMI & USB Extender is included
- 3 to 1 / 4 to 1 KVM Switch Extender Options



### ADM-2100AP-00A/00E Series

(ADM-2119AP-00A/00E / ADM-2121AP-00A/00E) Panel Mount KVM Extender Integrated 19/21.5-inch LCD Touch Display Monitor. True one-cable solution up to 100 meters CAT6 cable, no power supply is required.

ADM-2119AP-00A/00E	ADM-2121AP-00A/00E
19 inch LCD Display, 1280 x 1024 resolutions	21.5 inch LCD Display, 1920 x 1080 resolutions

Projected Capacitive Touch Screen

Aluminum or Stainless-Steel Bezel

- · Bezel meets NEMA 4X / IP66 requirements Built-in a 2-port USB 2.0 hub to support multiple USB
- devices • Built-in a 2-port 100BaseT Ethernet pass-through hub Single CAT6 cable connection to KVM Transmitter
- No Power Supply is required



### ADM-2100BP-00A Series

(ADM-2116BP-00A / ADM-2118BP-00A / ADM-2121BP-00A / ADM-2132BP-00A / ADM-2155BP-00A) VESA Mount 15.6/18.5/21.5/32/55-inch KVM Extender Integrated LCD Touch Display Monitor. True one-cable solution up to 100 meters CAT6 cable.

ADM-2116BP	ADM-2118BP	ADM-2121BP	ADM-2132BP	ADM-2155BP
-00A	-00A	-00A	-00A	-00A
15.6-inch LCD Display,	18.5-inch LCD Display,	21.5 inch LCD Display,	32-inch LCD Display,	55-inch LCD Display,
1920 x 1080 resolution	1920 x 1080 resolutions	1920 x 1080 resolutions	1920 x 1080 resolutions	1920 x 1080 resolutions
No Power Supply is required		-	-	
<ul> <li>Built-in a 2-port USB 2.0 hub to support multiple USB devices.</li> <li>Built-in a 2-port 100BaseT Ethernet pass-through hub</li> <li>Single CAT6 cable connection to KVM Transmitter</li> </ul>		Black Color Powder     Projected Capacitive     Enclosure meets IP5	e Touch Screen	







sales@goarista.com www.aristaipc.com



### **Pharmaceutical and Biotech Solutions**

Feature Products

**Industrial Extenders** 

### **KVM Extender Integrated Displays**

### ADM-2121AX-00A

Waterproof KVM Extender Integrated 21.5-inch LCD Touch Display Monitor.True one-cable solution up to 100 meters CAT6 cable, no power supply is required

- 21.5-inch LCD Display, 1920 x 1080 resolutions
- Projected Capacitive Touch Screen
- Waterproof Stainless-Steel Enclosure
- · Enclosure meets NEMA 4X / IP66 requirements
- · Built-in a 2-port USB 2.0 hub to support multiple USB devices.
- Built-in a 1-port 100BaseT Ethernet pass-through Single CAT6 cable connection to KVM Transmitter
- · No Power Supply is required



### ADM-5800AX-00A Series

(ADM-5815AX-00A / ADM-5817AX-00A / ADM-5819AX-00A) Waterproof KVM Extender Integrated 15/17/19-inch LCD Touch Display Monitor. True one-cable solution up to 100 meters CAT6 cable, no power supply is required

ADM-5815AX-00A	ADM-5817AX-00A	ADM-5819AX-00A
15-inch	17-inch	19-inch
LCD Display,	LCD Display,	LCD Display,
1024 x 768	1280 x 1024	1280 x 1024
resolutions	resolutions	resolutions

5-Wire Resistive Touch Screen

- Waterproof Stainless-Steel Enclosure
- Enclosure meets NEMA 4X / IP66 requirements
- Built-in a 2-port USB 2.0 hub to support multiple USB devices.
- Built-in a 1-port 100BaseT Ethernet pass-through
- · Single CAT6 cable connection to KVM Transmitter
- · No Power Supply is required

### ADM-5842AX-00A

Waterproof KVM Extender Integrated 42-inch LCD Touch Display Monitor

- · 42-inch LCD Display, 1920 x 1080 resolutions
- IR Touch Screen
- Waterproof Stainless-Steel Enclosure
- · Enclosure meets NEMA 4X / IP66 requirements · Built-in a 2-port USB 2.0 hub to support multiple USB devices.
- Built-in a 1-port 100BaseT Ethernet pass-through
- Single CAT6 cable connection to KVM Transmitter
- 24VDC Operating Voltage

**Industrial Extenders** 



### MicroBox-1200A

Fanless Compact Industrial Computer with integrated KVM Extension Transmitter

- · Computer and KVM extender all in one unit
- · Extends the computer's HDMI video, RS-232, USB signals to a remote location
- · Eliminates cables connection between transmitter and computer for quick deployment of event controller
- · A swappable modular design providing maximum flexibility of configuration to fit highly dynamic event requirements
- Swappable modular design to obtain minimum maintenance and upgrade efforts requirement
- · HDBaseT transmitter supports PoE to power the receiver unit at a remote location

•\_\_\_\_\_\_• • • • \_\_\_\_\_\_\_

### RS-123-E01-A07

Rack Mount Remote Computer/ Wall Mount HDBaseT Extender

- Standard 1RU height, 7" in depth 19" rack mount
- · Computer and KVM extender all in one unit
- Extends computer's HDMI video, RS-232, USB signals to remote location
- · Eliminates cables connection between transmitter and computer for quick deployment of event controller
- Swappable modular design providing maximum flexibility of configuration to fit highly dynamic event requirements
- Swappable modular design to obtain minimum maintenance and upgrade efforts requirement
- · HDBaseT transmitter supports PoE to power the receiver unit at remote location
- Computer module is equipped with 1.9GHz E3845 Quad-Core Atom CPU, up to 8GB DDR-3 memory

Reseller / SI info.





