



ThinManager Ready Thin Clients

Thin clients are a cost-effective solution providing manufacturing users with a safe and reliable environment. Their implementation with ThinManager Ready hardware ensures that it complements the manufacturing work environment and allows them to organize their process more efficiently; they reduce overall hardware issues with an improved response time. Moreover, its installation is quite simple and does not interfere with existing work processes. With a thin client surroundings, users are able to work in a collaborative environment with remote sharing and centralized access to information.

WHO WE ARE

ARISTA Corporation was founded in 1994 and has been providing computing platforms to various industries, like Pharmaceutical and biotech, Oil and Gas, Food and Beverage, Automotive, Logistic, FMCG, etc. ARISTA is committed to providing the most reliable computing platforms to optimize our customers' manufacturing automation systems. "Talk to us. We listen." makes ARISTA a dependable and accountable partner to all our customers.

WHY CHOOSE US



Longevity



Revision
Control



Flexible
Customization





Control Room Thin Clients

AP-3500-E01/H01-003

Multiple HDMI Outputs Thin Client by Desktop / VESA Mount Type

- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU; Celeron 3955U @ 2.00GHz
- 4GB DDR3 / 4GB DDR4 SO-DIMM
- Dual 1080p / 3x 4K HDMI
- Dual Gigabit Ethernet
- ThinManager Ready, PXE Boot
- Desktop or VESA Mount Available

4K Resolution Industrial Thin Clients / Multi-Monitor Thin Clients

AP-3500-H01-003

Multiple HDMI Outputs Office Grade Thin Client

- Intel Celeron 3955U @ 2.00GHz
- 4GB DDR4 SO-DIMM
- 3x 4K HDMI
- Dual Gigabit Ethernet
- ThinManager Ready, PXE Boot
- Desktop or VESA Mount Available



4K Resolution Industrial Thin Clients / Multi-Monitor Thin Clients

BoxPC-138-H01B-003

ThinManager Ready Triple 4K HDMI Thin Client

- Intel i7-6700T CPU
- 16GB DDR4 SO-DIMM
- Triple 4K HDMI Thin Client
- Dual Gigabit Ethernet
- ThinManager Ready, PXE Boot



4K Resolution Industrial Thin Clients / Multi-Monitor Thin Clients

BoxPC-138-H01B-00F

ThinManager Ready Thin Client with 7x 4K HDMI Outputs

- Intel i7-6700T CPU
- 16GB DDR4 SO-DIMM
- 7x 4K HDMI Outputs
- Dual Gigabit Ethernet
- ThinManager Ready, PXE Boot



4K Resolution Industrial Thin Clients / Multi-Monitor Thin Clients / Industrial Thin Clients

MiniBox-131-H01-003

Expandable Fanless Computer with Intel Celeron 3955U @ 2.00GHz, Fanless, 12VDC, mPCIe Expansion Slot

- Intel Celeron 3955U @ 2.00GHz
- Up to 4GB DDR4 SO-DIMM Memory
- 3 x 4K HDMI
- 1 x Gigabit LAN
- 6 x USB (4x USB 3.0, 2 x USB 2.0)
- ThinManager Ready, PXE Boot
- 12VDC Operating Input Voltage
- Wall Mount
- Fanless



4K Resolution Industrial Thin Clients / Multi-Monitor Thin Clients

BoxPC-203-G01-00F

Four 4K HDMI Outputs Thin Client

- Intel i7-3630QM CPU
- 8GB DDR3 SO-DIMM
- Four 4K HDMI
- Dual Gigabit Ethernet
- ThinManager Ready





Multi-Monitor Thin Clients

BoxPC-138-G01-00D

Five 1080p HDMI Outputs
Thin Client

- Intel i7-3630QM CPU
- 8GB DDR3 SO-DIMM
- Five 1080p HDMI
- Dual Gigabit Ethernet
- ThinManager Ready, PXE Boot



Industrial Thin Clients

MicroBox-1200A-E01 -003-DR

Wall Mount / DIN Rail Mount
Industrial Thin Client

- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Dual Gigabit Ethernet
- 1 x RS-232/422/485 BIOS Selectable
- 4 x USB 2.0 ports
- 330 feet Remote KVM Extension
- ThinManager Ready



Industrial Thin Clients

MicroBox-7824B-E02 -A03-SP

Industrial Thin Client with
Integrated Speakers

- Alert Applications Ready Thin Client
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Dual Gigabit Ethernet
- 1 x RS-232/422/485 BIOS Selectable
- 1 x USB 3.0, 3/6 x USB 2.0 ports
- Line out, Mic in
- Integrated two 3 watts Speakers
- ThinManager Ready



Industrial Thin Clients

MicroBox-7824B-E01 -003

Multiple HDMI Outputs Industrial
Thin Client

- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Dual Gigabit Ethernet
- 4 x RS-232/422/485 BIOS Selectable
- 1 x USB 3.0, 3 x USB 2.0 ports
- ThinManager Ready



Rack Mount Thin Clients

RS-102AT-G01-00D

Rack Mount Thin Client with
Intel i7-3630QM CPU

- Intel i7-3630QM
- 8GB DDR3 SO-DIMM Memory
- Dual Gigabit LAN
- 4 x USB 2.0, 2 x USB 3.0
- ThinManager Ready, PXE



Rack Mount Thin Clients

RS-103-H01-003

Rack Mount Thin Client with
Intel Celeron 3955U

- Intel Celeron 3955U
- 4GB DDR4 SO-DIMM
- 1 x Gigabit LAN
- 6 x USB (4 x USB 3.0, 2 x USB 2.0)
- ThinManager Ready, PXE





Panel Mount Thin Client Panel PCs

ARP-3600AP-E01-003 Series

Panel Mount Thin Client Panel PC with 10.4~24 inch 5-Wire Resistive Touch

- 10.4~24" LCD
- 5-Wire Resistive Touch
- Aluminum or Stainless-Steel Bezel
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Dual Gigabit Ethernet
- 4 x RS-232/422/485 BIOS Selectable
- 1 x USB 3.0, 3 x USB 2.0 ports

ARP-3610AP-E01-003	ARP-3615AP-E01-003	ARP-3617AP-E01-003	ARP-3619AP-E01-003	ARP-3621AP-E01-003	ARP-3624AP-E01-003
10.4" LCD, 800 x 600 Resolution	15" LCD, 1024 x 768 Resolution	17" LCD, 1280 x 1024 Resolution	19" LCD, 1280 x 1024 Resolution	21.5" LCD, 1920 x 1080 Resolution	24" LCD, 1920 x 1080 Resolution



Panel Mount Thin Client Panel PCs

ARP-3800AP-E01-003 Series

Panel Mount Thin Client Panel PC with 10.1~24 inch PCAP Touch Screen

- 10.1~24" LCD
- Projected Capacitive Touch Screen
- Aluminum or Stainless-Steel 316L Flush Bezel
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU; Intel i7-6600U CPU
- 4GB DDR3 SO-DIMM
- Dual Gigabit Ethernet
- 4 x RS-232/422/485 BIOS Selectable
- 1 x USB 3.0, 3 x USB 2.0 ports

ARP-3811AP-E01-003	ARP-3815AP-E01-003	ARP-3816AP-E01-003	ARP-3818AP-E01-003	ARP-3819AP-E01-003	ARP-3821AP-E01-003	ARP-3824AP-E01-003
10.1" LCD, 1280 x 800 Resolution	15" LCD, 1024 x 768 Resolution	15.6" LCD, 1920 x 1080 Resolution	18.5" LCD, 1920 x 1080 Resolution	19" LCD, 1280 x 1024 Resolution	21.5" LCD, 1920 x 1080 Resolution	24" LCD, 1920 x 1080 Resolution



Hazardous Areas C1D2 Thin Client Panel PCs

ARP-2200AP-G01-002-C1D2 Series

Class I, Div 2 Location Panel Mount Thin Client Panel PC with 15~21.5 inch 5-Wire Resistive Touch

- Preventing Combustible Dust Explosions with cUL Class I, Division 2
- 15~21.5" LCD
- 5-Wire Resistive Touch
- Aluminum or Stainless-Steel Bezel
- Intel i7-3612QM CPU
- 8GB DDR3 SO-DIMM
- Dual Gigabit Ethernet
- 2 x RS-232/422/485 BIOS Selectable
- 4 x USB 3.0, 2 x USB 2.0 ports
- ThinManager Ready

ARP-2215AP-G01-002-C1D2	ARP-2217AP-G01-002-C1D2	ARP-2219AP-G01-002-C1D2	ARP-2221AP-G01-002-C1D2
15" LCD, 1024 x 768 Resolution	17" LCD, 1280 x 1024 Resolution	19" LCD, 1280 x 1024 Resolution	21.5" LCD, 1920 x 1080 Resolution





Waterproof Thin Client Panel PCs

ARP-5500AX-E01-007 Series

NEMA 4X Waterproof Thin Client Panel PC with 15~19-inch Touch Screen

- 15~19" LCD
- 5-Wire Resistive Touch
- Stainless Steel 316L Enclosure
- Meets NEMA 4X requirements
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Gigabit Ethernet
- 2x USB 2.0 ports
- Optional UL Class 1 Division 2 of Hazardous Area Approved Configuration can Prevent Combustible Dust Explosion

Thin Client Panel PCs Powered by PoE

ARP-5500AX-E01-A06 Series

NEMA 4X Waterproof Thin Client Panel PC with 15~19-inch Touch Screen Powered by 802.3bt Type 3 or Type 4 PoE

- 15~19" LCD
- 5-Wire Resistive Touch
- Stainless Steel 316L Enclosure
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- 1x Gigabit Ethernet
- 2x USB 2.0 ports
- Powered By 802.3bt Type 3 or Type 4 PoE



Hazardous Areas C1D2 Thin Client Panel PCs

ARP-5500AX-E01-006 -C1D2 Series

Class I, Div 2 Location and NEMA 4X Waterproof Thin Client Panel PC with 15~19-inch Touch Screen

- Preventing Combustible Dust Explosions with cUL Class I, Division 2
- 15~19" LCD
- 5-Wire Resistive Touch
- Stainless Steel 316L Enclosure
- Meets NEMA 4X requirements
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Gigabit Ethernet
- 2x USB 2.0 ports



WIFI Boot ThinManager Ready Panel PC Thin Clients

ARP-5500AX-K01 Series

NEMA 4X Waterproof and WIFI Boot ThinManager Ready Panel PC Thin Client with 15~19-inch Resistive Touch Screen

- 15~19" LCD
- 5-Wire Resistive Touch Screen
- Stainless Steel Enclosure meets NEMA 4X Requirements
- Intel N200 CPU
- Up to 16GB DDR4 SO-DIMM
- 2 x Gigabit; 1 x 2.5GB, 1 x Gigabit
- 2 x USB 2.0 ports
- ThinManager WIFI Boot

ARP-5515AX	ARP-5517AX	ARP-5519AX
15" LCD, 1024 x 768 Resolution	17" LCD, 1280 x 1024 Resolution	19" LCD, 1280 x 1024 Resolution



WIFI Boot ThinManager Ready Panel PC Thin Clients

MicroBox-7521B-K01 -003-001

WIFI Boot ThinManager Ready Thin Client

- Intel 12th Gen N200 CPU
- Up to 16GB DDR4 SO-DIMM
- D1 x 2.5 Gigabit, 1 x Gigabit
- DP + HDMI Dual Display Ports
- 3 x USB 3.2, 1 x USB 2.0
- 24VDC Operating Input Voltage
- ThinManager WIFI Boot



Waterproof Thin Client Panel PCs

ARP-3824AX-E01-007

NEMA 4X / IP66 Waterproof Thin Client Panel PC with 24-inch PCAP Touch Screen

- 24" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch Screen
- Stainless Steel 316L Enclosure
- Meets NEMA 4X / IP66 requirements
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Gigabit Ethernet
- 2x USB 2.0 ports

Thin Client Panel PCs Powered by PoE

ARP-3824AX-E01-A06

NEMA 4X / IP66 Waterproof Thin Client Panel PC with 24-inch PCAP Touch Screen Powered by 802.3bt Type 3 or Type 4 PoE

- 24" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch
- Stainless Steel 316L Enclosure
- Meets NEMA 4X / IP66 requirements
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- 1x Gigabit Ethernet
- 2x USB 2.0 ports
- Powered by 802.3bt Type 3 or Type 4 PoE



WIFI Boot ThinManager Ready Panel PC Thin Clients

ARP-3824AX-K01

NEMA 4X Waterproof WIFI Boot ThinManager Ready Panel PC Thin Client with 24-inch PCAP Touch Screen

- 24" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch
- Stainless Steel Enclosure meets NEMA 4X Requirements
- Intel N200 CPU
- Up to 16GB DDR4
- 1 x 2.5G, 1 x 1G Ethernet
- 2 x USB 2.0 ports
- ThinManager WIFI Boot
- 802.11ax WIFI



Large Format Thin Client Panel PCs / Waterproof Thin Client Panel PCs

ARP-5542AX-E01-007

NEMA 4X Thin Client Panel PC with 42 inch IR Touch Screen

- 42" LCD, 1920 x 1080 Resolution
- IR Touch or Tempered Glass
- Stainless Steel 316L Enclosure
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Gigabit Ethernet
- 2x USB 2.0 ports



Large Format Thin Client Panel PCs / VESA Mount Thin Client Panel PCs

ARP-3855BP-E01-003

VESA Mount Thin Client Panel PC with 55 inch PCAP Touch Screen

- 55" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch Screen
- VESA Mount / Wall Mount
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Dual Gigabit Ethernet
- 2 x RS-232/422/485 BIOS Selectable
- 1 x USB 3.0, 3 x USB 2.0 ports
- Line Out, Mic In
- ThinManager Ready



Waterproof Thin Client Panel PCs

ARP-D24AX-E01-007

Dual NEMA 4X / IP66 Waterproof Thin Client Panel PC with 24-inch PCAP Touch Screen

- Dual 24" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch
- Stainless Steel 316L Enclosure
- Meets NEMA 4X / IP66 requirements
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- Up to 4GB DDR3L SO-DIMM
- 1x Gigabit Ethernet
- 2x USB 2.0 ports





Waterproof Thin Client Panel PCs

ARP-3821AX-E01-007

NEMA 4X / IP66 Waterproof Thin Client Panel PC with 21.5-inch PCAP Touch Screen

- 21.5" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch Screen
- Stainless Steel 316L Enclosure
- Meets NEMA 4X / IP66 requirements
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Gigabit Ethernet
- 2x USB 2.0 ports

Thin Client Panel PCs Powered by PoE

ARP-3821AX-E01-A06

NEMA 4X / IP66 Waterproof Thin Client Panel PC with 21.5-inch PCAP Touch Screen Powered by 802.3bt Type 3 or Type 4 PoE

- 21.5" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch Screen
- Stainless Steel 316L Enclosure
- Meets NEMA 4X / IP66 requirements
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- 1x Gigabit Ethernet
- 2x USB 2.0 ports
- Powered By 802.3bt Type 3 or Type 4 PoE



Hazardous Areas C1D2 Thin Client Panel PCs

ARP-3821AX-E01-006-C1D2

Class I, Div 2 Location and NEMA 4X / IP66 Waterproof Thin Client Panel PC with 21.5-inch PCAP Touch Screen

- Preventing Combustible Dust Explosions with cUL Class I, Division 2
- 21.5" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch Screen
- Stainless Steel 316L Enclosure
- Meets NEMA 4X / IP66 requirements
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Gigabit Ethernet
- 2x USB 2.0 ports



WIFI Boot ThinManager Ready Panel PC Thin Clients

ARP-3821AX-K01

NEMA 4X Waterproof WIFI Boot ThinManager Ready Panel PC Thin Client with 21.5-inch PCAP Touch Screen

- 21.5" LCD, 1920 x 1080 Resolution
- Projected Capacitive Touch
- Stainless Steel Enclosure meets NEMA 4X Requirements
- Intel N200 CPU
- Up to 16GB DDR4
- 1 x 2.5G, 1 x 1G Ethernet
- 2 x USB 2.0 ports
- ThinManager WIFI Boot
- 802.11ax WIFI



Versatile Mounting Options for Every Environment



48460 Lakeview Blvd,
Fremont, CA 94538



www.aristaipc.com



sales@goarista.com



+1-510-226-1800



VESA Mount Thin Client Panel PCs

ARP-3800BP-E01-003 Series

VESA Mount Thin Client Panel PC with 15.6~24 inch PCAP Touch Screen

- 15.6~24" LCD
- Projected Capacitive Touch Screen
- VESA Mount / Wall Mount
- Intel Celeron J1900 @ 1.99GHz / Atom E3845 @ 1.91GHz CPU
- 4GB DDR3 SO-DIMM
- Dual Gigabit Ethernet
- 2 x RS-232/422/485 BIOS Selectable
- 1 x USB 3.0, 3 x USB 2.0 ports
- Line Out, Mic In
- ThinManager Ready

Thin Client Panel PCs Powered by PoE

ARP-3800BP-K01 Series

VESA Mount Thin Client Panel PC with 15.6~24-inch PCAP Touch Screen Powered by PoE 802.3bt Type 3/4

- 15.6~24" LCD
- Projected Capacitive Touch Screen
- Intel N200 CPU
- Up to 16GB DDR4
- 1 x 2.5G, 1 x 1G Ethernet
- 3 x USB 3.2, 1 x USB 2.0 ports
- Optional M.2 NVMe SSD
- ThinManager Ready
- Powered By PoE 802.3bt Type 3/4



WIFI Boot ThinManager Ready Panel PC Thin Clients

ARP-3800BP-K01 Series

VESA Mount WIFI Boot ThinManager Ready Panel PC Thin Client with 15.6~24-inch PCAP Touch Screen

- 15.6~24" LCD
- Projected Capacitive Touch Screen
- Intel N200 CPU
- Up to 16GB DDR4
- 1 x 2.5G, 1 x 1G Ethernet
- 3 x USB 3.2, 1 x USB 2.0 ports
- ThinManager WIFI Boot
- 802.11ax WIFI

ARP-3816BP	ARP-3818BP	ARP-3821BP	ARP-3824BP
15.6" LCD, 1920 x 1080 Resolution	18.5" LCD, 1920 x 1080 Resolution	21.5" LCD, 1920 x 1080 Resolution	24" LCD, 1920 x 1080 Resolution

Reseller / SI info.



48460 Lakeview Blvd,
Fremont, CA 94538



www.aristaipc.com



sales@goarista.com



+1-510-226-1800